1	What is claimed as being new and desired to be protected by Letters Patent of
2	the United States is as follows:
.3	(1) An accessory for shoelaces comprising three model combinations:
4	(a) model #1 comprising in combination;
5	a two piece shoelace cover for one shoe;
6	an aperture in each said piece of said cover;
7	a first attachment means attached to each said piece of said cover;
8	a second attachment attached means to each said piece of said cover;
9	a third attachment means attached to said shoe; and
10	(b) model #2 comprising in combination;
11	a two piece shoelace cover for one shoe;
12	an aperture in each said piece of said cover;
13	a first attachment means for each said piece of said cover; and
14	(c) model #3 comprising in combination;
15	a one piece shoelace cover for one shoe;
16	an aperture in both sides of said cover;
17	a first attachment means in both sides of said cover; and
18	said three models each have their own individual sequence of installation so as
19	each selected model provide the same safety means by encapsulating the bow and
20	tied shoelace end for each of the styles so the person wearing said shoe style will
21	not trip and fall while each said model prevents said shoe lace from becoming
22	untied thereby creating a convenient safety factor for said shoe wearer while each
23	said model is made of a soft flexible material such as cloth or the like, and is
24	attachable to any style shoe, said styles color coordinate to match any shoe such as

a dress shoe or a sports shoe such as a running shoe wherein said covers for said

running shoe may of a material having a glow in the dark accent to help protect

25

26

- runners; further, an option, within said invention, is for a manufacturer of said shoe to select one or all of said models, manufacture said model, and add said model directly to said manufacture's line of shoes.
 - (2) The invention as claimed in claim 1 wherein said two piece cover, in model #1, is of a left and right side design for said one shoe; said aperture is located at the front end of each said piece so as to accept and retain said shoelace; said first attachment means for each said piece provides a male and a female two piece means which when mated together provide said encapsulation means for said eye and said tied shoelace end for each said piece; said second attachment means being the female portion of said cover said portion aligns and mates to said shoe male snap thereby providing said means for said cover to be attached to said shoe; and a third attachment means, being the male portion of said snap means is permanently attached to said shoe wherein said male snap aligns with said female snap on said cover end thereby securing said shoe to said cover while both sides of said shoe have the same cover arrangement which thereby provide a sequence of installation for both said covers.
 - (3) The invention as claimed in claim 1 wherein said two piece cover, in model #2, is of a left and right side design for said one shoe, said aperture is located at the front end of each said piece so as to accept and retain said shoelace; said first attachment means in said model #2 being a "U" shaped clip, preferably plastic, which when said cover is folded over said edge of said shoe said clip presses down over said cover and said shoe edge thereby retaining said cover to said shoe while both sides of said shoe have the same cover arrangement which thereby provide a sequence of installation for both said covers.
 - (4) The invention as claimed in claim 1 wherein said one piece cover, in model #3, folds down into said shoe itself whereby the arch and weight of the person's foot holds said model #3 cover in place while said apertures in both said sides of said cover are located at the front end so as to accept and retain said shoelace said first attachment means for said cover is provided on both sides of said cover

- wherein a male and a female two piece snap means, which when mated together,
- 2 said first attachment means provides said encapsulation means for said eye and
- 3 said tied shoelace ends for both sides of said cover thereby creating a sequence of
- 4 installation for said single piece cover.

14

15

16

24

25

26

28

- (5) The invention as claimed in claim 1 wherein all three models provide the
 same said aperture means.
- (6) The invention as claimed in claim 1 wherein all three models provide an
 encapsulation system for said shoelaces on said shoes.
- 9 (7) The invention as claimed in claim 1 wherein said attachment means provide 10 a means so as to attach said covers to said shoes.
- 11 (8) The invention as claimed in claim 1 wherein all three models provide the 12 same safety means for the shoe wearer wherein said laces will not come untied 13 thereby creating a safety factor so said wearer will not trip and fall.
 - (9) The invention as claimed in claim 1 wherein said covers in all said models is made of a soft flexible material, such as cloth, or the like, said cover material being capable of flexibly folding so as to provide said encapsulation means.
- 17 (10) The invention as claimed in claim 1 wherein all said model covers have color styles so as to coordinate and match any shoe.
- 19 (11) The invention as claimed in claim 1 wherein said cover for all said models 20 is attachable to any shoe.
- 21 (12) The invention as claimed in claim 1 wherein said cover, in all said models, 22 is preferably designed so as to coordinate with any dress shoe, any sports shoe and 23 any running shoe.
 - (13) The invention as claimed in claim 1 wherein said cover, for all three models, is designed for any running shoe said cover being of a material so as to create a glow in the dark factor thereby creating safety to help protect runners.

27 * * * * * * *